

RAPID 0

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, RAPID'S BLEND OF FLAT-BAR CONTROL AND ROAD BIKE SPEED IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	White/Red/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact, flat 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Connect SL, 30.9
	SADDLE	Selle Royal Seta M
	PEDALS	Shimano M505
DRIVETRAIN	SHIFTERS	Shimano R770
	FRONT DERAILLEUR	Shimano R440
	REAR DERAILLEUR	Shimano 105
	BRAKES	Shimano Dual Pivot, Long Reach
	BRAKE LEVERS	Tektro Alloy
	CASSETTE	Shimano 105 12x25, 10-speed
	CHAIN	Shimano 105
	CRANKSET	Shimano R600, 34/50
	BOTTOM BRACKET	Shimano, External
WHEELS	RIMS	Mavic Aksium Race
	HUBS	Mavic Aksium Race
	SPOKES	Mavic Aksium Race
	TIRES	Michelin Lithion, 700x25 Folding
	EXTRAS	Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

It's versatile, it's inviting, and most importantly, it's a bike you'll want to ride every day. With high-quality ALUXX SL aluminum tubing and comfortable, stretched-out flat-bar geometry, Rapid is your ticket to improved fitness or a stress-free commute—or both.



KEY UPGRADES (OVER RAPID 1)

- Smooth-shifting Shimano 105, 10-speed drivetrain
- Lightweight Giant Connect SL aluminum stem
- Lightweight Mavic Aksium wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380762	71.0	74.0	53.5	12.5	42.5	100.8	29.1
S/46.5 cm	380763	72.0	74.0	55.0	14.5	42.5	101.5	30.3
M/50.0 cm	380764	72.5	73.0	56.5	16.5	42.5	101.5	31.0
L/55.5 cm	380765	72.5	73.0	59.5	20.5	42.5	103.3	32.5
XL/58.5 cm	380766	72.5	72.5	61.5	22.5	42.5	105.3	33.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

RAPID 1

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, RAPID'S BLEND OF FLAT-BAR CONTROL AND ROAD BIKE SPEED IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	White/Silver/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect, flat 31.8
	STEM	Giant Connect
	SEATPOST	Giant Connect SL, 30.9
	SADDLE	Selle Royal Seta M
	PEDALS	Shimano M505
DRIVETRAIN	SHIFTERS	Shimano R440
	FRONT DERAILLEUR	Shimano R440
	REAR DERAILLEUR	Shimano 105
	BRAKES	Shimano Dual Pivot, Long Reach
	BRAKE LEVERS	Tektro Alloy
	CASSETTE	Shimano HG-50 12x25, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano Tiagra, 34/50
	BOTTOM BRACKET	Shimano, External
	WHEELS	RIMS
HUBS		Formula sealed Cartridge Bearing 24/28h
SPOKES		SAPIM Race, 14/15g
TIRES		Kenda Kriterium, 700x25
EXTRAS		Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

It's versatile, it's inviting, and most importantly, it's a bike you'll want to ride every day. With high-quality ALUXX SL aluminum tubing and comfortable, stretched-out flat-bar geometry, Rapid is your ticket to improved fitness or a stress-free commute—or both.



KEY UPGRADES (OVER RAPID 2)

- Shimano compact Tiagra Crankset
- Giant Connect SL composite seatpost
- Formula sealed cartridge hubs/ SAPIM Race spokes/Mavic CXP22 rim, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	381062	71.0	74.0	53.5	12.5	42.5	100.8	29.1
S/46.5 cm	381063	72.0	74.0	55.0	14.5	42.5	101.5	30.3
M/50.0 cm	381064	72.5	73.0	56.5	16.5	42.5	101.5	31.0
L/55.5 cm	381065	72.5	73.0	59.5	20.5	42.5	103.3	32.5
XL/58.5 cm	381066	72.5	72.5	61.5	22.5	42.5	105.3	33.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

RAPID 2

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, RAPID'S BLEND OF FLAT-BAR CONTROL AND ROAD BIKE SPEED IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L,XL
	COLORS	White/Blue/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect, flat 31.8
	STEM	Alloy adjustable height
	SEATPOST	Giant Connect, 30.9
	SADDLE	Giant Performance Road, Men's
DRIVETRAIN	PEDALS	Caged w/Clips
	SHIFTERS	Shimano R440
	FRONT DERAILLEUR	Shimano R453
	REAR DERAILLEUR	Shimano Tiagra
	BRAKES	Alloy Dual Pivot
	BRAKE LEVERS	Tektro Alloy
	CASSETTE	Shimano HG-50 12x25, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	FSA Omega Mega Exo, 30/39/50
	BOTTOM BRACKET	FSA Mega Exo
WHEELS	RIMS	Giant Sport Road, Double Wall
	HUBS	[F] Formula Sealed, [R] Shimano 2200, 32h
	SPOKES	Stainless Steel
	TIRES	Kenda Kwest, 700x28
	EXTRAS	Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

It's versatile, it's inviting, and most importantly, it's a bike you'll want to ride every day. With high-quality ALUXX SL aluminum tubing and comfortable, stretched-out flat-bar geometry, Rapid is your ticket to improved fitness or a stress-free commute—or both.



KEY UPGRADES (OVER RAPID 3)

- Advanced-Grade composite fork
- Shimano 9-speed drivetrain
- Lighter FSA Omega triple crankset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380562	71.0	74.0	53.5	12.5	42.5	100.8	29.1
S/46.5 cm	380563	72.0	74.0	55.0	14.5	42.5	101.5	30.3
M/50.0 cm	380564	72.5	73.0	56.5	16.5	42.5	101.5	31.0
L/55.5 cm	380565	72.5	73.0	59.5	20.5	42.5	103.3	32.5
XL/58.5 cm	380566	72.5	72.5	61.5	22.5	42.5	105.3	33.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

RAPID 3

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, RAPID'S BLEND OF FLAT-BAR CONTROL AND ROAD BIKE SPEED IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Silver/White/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	CroMo, OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Connect, flat 31.8
	STEM	Alloy adjustable height
	SEATPOST	Giant Connect, 30.9
	SADDLE	Giant Performance Road, Men's
	PEDALS	Caged w/ Clips
DRIVETRAIN	SHIFTERS	Shimano R221 EZ Fire
	FRONT DERAILLEUR	Shimano R443
	REAR DERAILLEUR	Shimano Sora
	BRAKES	Alloy Dual Pivot
	BRAKE LEVERS	Generic Alloy
	CASSETTE	SRAM PG 830 11x28, 8-speed
	CHAIN	KMC Z72
	CRANKSET	FSA Tempo, 30/42/52
	BOTTOM BRACKET	FSA Cartridge
	WHEELS	RIMS
HUBS		[F] Formula Sealed, [R] Shimano 2200, 32h
SPOKES		Stainless Steel
TIRES		Kenda Kwest, 700x28
EXTRAS		Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

It's versatile, it's inviting, and most importantly, it's a bike you'll want to ride every day. With high-quality ALUXX SL aluminum tubing and comfortable, stretched-out flat-bar geometry, Rapid is your ticket to improved fitness or a stress-free commute—or both.



FEATURES

- CroMo fork
- Wide-range 8-speed Shimano shifting with FSA Tempo triple crankset
- Giant Performance Road saddle

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380062	71.0	74.0	53.5	12.5	42.5	100.8	29.1
S/46.5 cm	380063	72.0	74.0	55.0	14.5	42.5	101.5	30.3
M/50.0 cm	380064	72.5	73.0	56.5	16.5	42.5	101.5	31.0
L/55.5 cm	380065	72.5	73.0	59.5	20.5	42.5	103.3	32.5
XL/58.5 cm	380066	72.5	72.5	61.5	22.5	42.5	105.3	33.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

DASH 0

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, ROAD BIKE SPEED AND FLAT-HANDLEBAR COMFORT IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L
	COLORS	White/Blue/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact, flat 31.8
	STEM	Giant Connect SL
	SEATPOST	Giant Connect SL Composite, 30.9
	SADDLE	Selle Royal Seta W
	PEDALS	Shimano M505
DRIVETRAIN	SHIFTERS	Shimano R770
	FRONT DERAILLEUR	Shimano R440
	REAR DERAILLEUR	Shimano 105
	BRAKES	Shimano Dual Pivot, Long Reach
	BRAKE LEVERS	Tektro Alloy
	CASSETTE	Shimano 105 12x25, 10-speed
	CHAIN	Shimano 105
	CRANKSET	Shimano R600, 34/50
	BOTTOM BRACKET	Shimano, External
WHEELS	RIMS	Mavic Aksium Race
	HUBS	Mavic Aksium Race
	SPOKES	Mavic Aksium Race
	TIRES	Michelin Lithion, 700x25 Folding
	EXTRAS	Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Imagine the speed and agility of a road-racing bike with the added comfort and control of a mountain-bike-inspired flat handlebar. With high-quality ALUXX SL aluminum tubing and agile, yet comfortable, geometry, Dash will coax you into riding every day.



KEY UPGRADES (OVER DASH 1)

- Smooth-shifting Shimano 105, 10-speed drivetrain
- Lightweight Giant Connect SL aluminum stem
- Lightweight Mavic Aksium wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380862	71.0	74.5	53.0	13.0	42.5	100.9	29.2
S/46.5 cm	380863	72.0	74.0	54.5	15.0	42.5	101.0	30.1
M/50.0 cm	380864	72.5	73.5	56.0	17.0	42.5	101.5	31.2
L/53.5	380865	72.5	73.0	57.5	19.0	42.5	102.5	32.1

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

DASH 1

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, ROAD BIKE SPEED AND FLAT-HANDLEBAR COMFORT IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L
	COLORS	White/Teal/Anthracite
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact, flat 31.8
	STEM	Giant Connect
	SEATPOST	Giant Connect SL Composite, 30.9
	SADDLE	Selle Royal Seta W
	PEDALS	Shimano M505
	DRIVETRAIN	SHIFTERS
FRONT DERAILLEUR		Shimano R440
REAR DERAILLEUR		Shimano 105
BRAKES		Shimano Dual Pivot, Long Reach
BRAKE LEVERS		Tektro Alloy
CASSETTE		Shimano HG50 12x25, 9-speed
CHAIN		Shimano HG-73
CRANKSET		Shimano Tiagra, 34/50
BOTTOM BRACKET		Shimano, External
WHEELS	RIMS	Mavic CXP22
	HUBS	Formula Sealed Cartridge Bearing, 24/28h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Kenda Kriterium, 700x25
	EXTRAS	Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Imagine the speed and agility of a road-racing bike with the added comfort and control of a mountain-bike-inspired flat handlebar. With high-quality ALUXX SL aluminum tubing and agile, yet comfortable, geometry, Dash will coax you into riding every day.



KEY UPGRADES (OVER DASH 2)

- Shimano compact Tiagra Crankset
- Giant Connect SL seatpost
- Formula sealed cartridge hubs/ SAPIM Race spokes/Mavic CXP22 rim, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	381162	71.0	74.5	53.0	13.0	42.5	100.9	29.2
S/46.5 cm	381163	72.0	74.0	54.5	15.0	42.5	101.0	30.1
M/50.0 cm	381164	72.5	73.5	56.0	17.0	42.5	101.5	31.2
L/53.5	381165	72.5	73.0	57.5	19.0	42.5	102.5	32.1

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

DASH 2

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, ROAD BIKE SPEED AND FLAT-HANDLEBAR COMFORT IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L
	COLORS	White/Green/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact, flat 31.8
	STEM	Alloy adjustable height
	SEATPOST	Giant Connect, 30.9
	SADDLE	Giant Performance Road, Women's
	PEDALS	Caged w/ Clips
DRIVETRAIN	SHIFTERS	Shimano R440
	FRONT DERAILLEUR	Shimano R453
	REAR DERAILLEUR	Shimano Tiagra
	BRAKES	Alloy Dual Pivot
	BRAKE LEVERS	Tektro Alloy
	CASSETTE	Shimano HG50 12x25, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	FSA Omega Mega Exo, 30/39/50
	BOTTOM BRACKET	FSA Mega Exo
WHEELS	RIMS	Giant Sport Road, Double Wall
	HUBS	[F] Formula Sealed, [R] Shimano 2200, 32h
	SPOKES	Stainless Steel
	TIRES	Kenda Kwest, 700x28
	EXTRAS	Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Imagine the speed and agility of a road-racing bike with the added comfort and control of a mountain-bike-inspired flat handlebar. With high-quality ALUXX SL aluminum tubing and agile, yet comfortable, geometry, Dash will coax you into riding every day.



KEY UPGRADES (OVER DASH 3)

- Advanced-Grade composite fork
- Shimano 9-speed drivetrain
- Lighter FSA Omega triple crankset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380662	71.0	74.5	53.0	13.0	42.5	100.9	29.2
S/46.5 cm	380663	72.0	74.0	54.5	15.0	42.5	101.0	30.1
M/50.0 cm	380664	72.5	73.5	56.0	17.0	42.5	101.5	31.2
L/53.5	380665	72.5	73.0	57.5	19.0	42.5	102.5	32.1

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

DASH 3

FOR FITNESS, COMMUTING OR JUST PLAIN FUN, ROAD BIKE SPEED AND FLAT-HANDLEBAR COMFORT IS THE SMART WAY TO GET THERE FASTER.



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L
	COLORS	White/Yellow/Silver
	FRAME	ALUXX SL-Grade Aluminum
	FORK	CroMo, OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Contact, flat 31.8
	STEM	Alloy adjustable height
	SEATPOST	Giant Connect, 30.9
	SADDLE	Giant Performance Road, Women's
	PEDALS	Caged w/ Clips
DRIVETRAIN	SHIFTERS	Shimano R221 EZ Fire
	FRONT DERAILLEUR	Shimano R443
	REAR DERAILLEUR	Shimano Sora
	BRAKES	Alloy Dual Pivot
	BRAKE LEVERS	Alloy
	CASSETTE	SRAM PG830 11x28, 8-speed
	CHAIN	KMC Z72
	CRANKSET	FSA Tempo, 30/42/52
	BOTTOM BRACKET	FSA Cartridge
WHEELS	RIMS	Giant Sport Road, Double Wall
	HUBS	[F] Formula Sealed, [R] Shimano 2200, 32h
	SPOKES	Stainless Steel
	TIRES	Kenda Kwest, 700x28
	EXTRAS	Alloy bar-ends

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Imagine the speed and agility of a road-racing bike with the added comfort and control of a mountain-bike-inspired flat handlebar. With high-quality ALUXX SL aluminum tubing and agile, yet comfortable, geometry, Dash will coax you into riding every day.



FEATURES

- CroMo fork
- Wide-range 8-speed Shimano shifting with FSA Tempo triple crankset
- Giant Performance Road women's saddle

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380162	71.0	74.5	53.0	13.0	42.5	100.9	29.2
S/46.5 cm	380163	72.0	74.0	54.5	15.0	42.5	101.0	30.1
M/50.0 cm	380164	72.5	73.5	56.0	17.0	42.5	101.5	31.2
L/53.5	380165	72.5	73.0	57.5	19.0	42.5	102.5	32.1

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

YUKON

ADVENTURE COMES IN ALL DIFFERENT FLAVORS.
CHOOSE YOUR OWN ROUTE—SMOOTH DIRT TRAILS OR
RUGGED SINGLETRACK—WITH YUKON OR YUKON FX.



SPECIFICATIONS

FRAME	SIZES	14(XS),16(S),18(M),20(L),22(XL),24(2XL)
	COLORS	Brushed/Blue, Brushed/Orange
	FRAME	ALUXX-Grade Butted Aluminum
	FORK	RockShox Dart 1, 100mm travel
	SHOCK	N/A
COMPONENTS	HANDLEBAR	Alloy, high rise 31.8mm
	STEM	Alloy
	SEATPOST	Alloy, 350x30.9mm
	SADDLE	Giant Sport MTB
	PEDALS	Alloy Platform
DRIVETRAIN	SHIFTERS	Shimano Alivio Rapidfire
	FRONT DERAILLEUR	Shimano Acera
	REAR DERAILLEUR	Shimano Deore
	BRAKES	AVID BB5
	BRAKE LEVERS	Tektro Alloy, 2-Finger
	CASSETTE	SRAM PG830 11x32, 8-speed
	CHAIN	KMC Z72
	CRANKSET	Truvativ ISO Flow 3.0, 22/32/42
	BOTTOM BRACKET	Cartridge
	WHEELS	RIMS
HUBS		Formula, 32h
SPOKES		Stainless Steel, 14g
TIRES		Kenda Nevegal, 26x2.1
EXTRAS		N/A

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

For hardtail agility on dirt paths or singletrack, the Yukon's lightweight ALUXX frame, with balanced geometry and roomy cockpit, offers comfort and control.



FEATURES

- RockShox Dart 1, 100mm suspension fork
- Shimano Alivio trigger shifting, Shimano Deore rear derailleur
- Avid BB5 mechanical disc brakes
- Giant XC Alloy rim/Formula disc hub, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches	Brushed/Blue	Brushed/Orange	degrees	degrees	inches	inches	inches	inches	inches
XS/14	333062	333162	70.0	74.0	20.9	4.6	16.7	40.2	29.1
S/16	333063	333163	70.0	73.0	22.4	4.6	16.7	41.3	29.1
M/18	333064	333164	70.0	73.0	22.8	5.7	16.7	41.8	29.5
L/20	333065	333165	70.0	73.0	23.3	6.3	16.7	42.3	30.7
XL/22	333066	333166	70.0	72.0	24.3	7.5	16.7	42.9	31.9
*2XL/24	333067	333167	70.0	72.0	24.8	7.9	16.7	43.4	32.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

RINCON

BLAZE NEW TRAILS ON A CLASSIC HARDTAIL. RINCON IS OFF-ROAD READY AND WAITING TO EXPLORE.



SPECIFICATIONS

FRAME	SIZES	14(XS),16(S),18(M),20(L),22(XL)	
	COLORS	Black, Satin Silver	
	FRAME	ALUXX-Grade Butted Aluminum	
	FORK	SR XCM w/ Preload Adjust, 100mm travel	
	SHOCK	N/A	
COMPONENTS	HANDLEBAR	Alloy, high rise 31.8mm	
	STEM	Alloy	
	SEATPOST	Alloy, 350x30.9mm	
	SADDLE	Giant Sport MTB	
	PEDALS	Alloy Platform	
	DRIVETRAIN	SHIFTERS	Shimano EF-50
		FRONT DERAILLEUR	Shimano M310
REAR DERAILLEUR		Shimano Alivio	
BRAKES		Tektro I.O. Disc	
BRAKE LEVERS		Shimano EF-50	
CASSETTE		SRAM PG820 11x32, 8-speed	
CHAIN		KMC Z72	
CRANKSET		SR XCT, 22/32/42	
	BOTTOM BRACKET	SR Cartridge	
WHEELS	RIMS	Giant XC Alloy, Double Wall	
	HUBS	Formula, 32h	
	SPOKES	Stainless Steel, 14g	
	TIRES	Kenda Nevegal, 26x2.1 (Black) Kenda Small Block 8, 26x2.1 (Satin Silver)	
	EXTRAS	N/A	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

With a lightweight, durable ALUXX aluminum frame built to maximize a 100-millimeter suspension fork, Rincon is ready to explore the path less traveled. Dependable components, including sturdy disc brakes, make it a fun and reliable adventure companion.



FEATURES

- SR XCM, 100mm suspension fork
- Shimano trigger shifting, Shimano Alivio rear derailleur
- Tektro mechanical disc brakes
- Giant XC Alloy rim/Formula disc hub, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
<i>inches</i>	<i>Black</i>	<i>Satin Silver</i>	<i>degrees</i>	<i>degrees</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
XS/14	332062	332162	70.0	74.0	20.9	4.6	16.7	40.2	29.1
S/16	332063	332163	70.0	73.0	22.4	4.6	16.7	41.3	29.1
M/18	332064	332164	70.0	73.0	22.8	5.7	16.7	41.8	29.5
L/20	332065	332165	70.0	73.0	23.3	6.3	16.7	42.3	30.7
XL/22	332066	332166	70.0	72.0	24.3	7.5	16.7	42.9	31.9

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

RINCON W

FOLLOW NEW TRAILS, FIND NEW ADVENTURES.
MAKE OFF-ROAD RIDING MORE FUN WITH AN
EASYGOING, COMFORTABLE COMPANION.



SPECIFICATIONS

FRAME	SIZES	12.5(2XS),14(XS),16(S),18(M)	
	COLORS	Silver/Red	
	FRAME	ALUXX-Grade Butted Aluminum	
	FORK	SR XCM w/ Preload Adjust, 100mm travel	
	SHOCK	N/A	
COMPONENTS	HANDLEBAR	Alloy, high rise 31.8mm	
	STEM	Alloy	
	SEATPOST	Alloy, 350x30.9	
	SADDLE	Giant Sport MTB Womens	
	PEDALS	Alloy Platform	
	SHIFTERS	Shimano EF-50	
	FRONT DERAILLEUR	Shimano C050	
DRIVETRAIN	REAR DERAILLEUR	Shimano Alivio	
	BRAKES	Tektro I.O. Disc	
	BRAKE LEVERS	Shimano EF-50	
	CASSETTE	SRAM PG820 11x32, 8-speed	
	CHAIN	KMC Z72	
	CRANKSET	SR XCT, 22/32/42	
	BOTTOM BRACKET	SR Cartridge	
	WHEELS	RIMS	Giant Alloy 32H, Double Wall
		HUBS	Formula Disc, 32h
		SPOKES	Stainless Steel, 14g
TIRES		Kenda Nevegal, 26x2.1	
EXTRAS		N/A	

FRAME TECHNOLOGY

With an aluminum, women's-specific frame, comfortable upright positioning and a trail-ready suspension fork, Rincon W is ready to explore the urban jungle or take to the trail. The choice is yours.



FEATURES

- SR XCM, 100mm suspension fork
- Shimano trigger shifting, Shimano Alivio rear derailleur
- Tektro mechanical disc brakes
- Giant XC Alloy rim/Formula disc hub, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
<i>inches</i>		<i>degrees</i>	<i>degrees</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
2XS/12.5	332561	70.5	74.0	20.3	3.9	16.7	40.0	27.3
XS/14	332562	70.5	73.0	21.1	4.6	16.7	40.0	27.9
S/16	332563	70.5	73.0	21.6	4.6	16.7	40.5	28.4
M/18	332564	70.0	73.5	22.4	4.9	16.7	40.9	29.5

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

Specifications and availability subject to change without notice.

BOULDER SE

THE DIRT PATH AT THE END OF THE STREET IS JUST WAITING TO BE EXPLORED. WHAT ARE YOU WAITING FOR?



SPECIFICATIONS

FRAME	SIZES	12.5(2XS),14(XS),16(S),18(M),20(L),22(XL)
	COLORS	Red, Satin Black
	FRAME	ALUXX-Grade Butted Aluminum
	FORK	SR XCM w/ Preload Adjust, 100mm travel
SHOCK		N/A
COMPONENTS	HANDLEBAR	Steel, 50mm rise
	STEM	Alloy
	SEATPOST	Alloy, 350x30.9mm
	SADDLE	Giant Sport MTB
	PEDALS	Nylon Platform
DRIVETRAIN	SHIFTERS	Shimano EF-50
	FRONT DERAILLEUR	Shimano C-102
	REAR DERAILLEUR	Shimano Acera
	BRAKES	Alloy Direct-Pull Cantilever
	BRAKE LEVERS	Shimano EF-50
	CASSETTE	Shimano 14x34, 7-speed
	CHAIN	KMC Z51
	CRANKSET	Suntour XCT V2, 28/38/48
	BOTTOM BRACKET	SR Cartridge
	WHEELS	RIMS
HUBS		Alloy, 32h
SPOKES		Stainless Steel, 14g
TIRES		MTB Trail 26x2.1 (Red), Kenda K-Rad 26x2.1 (Satin Black)
EXTRAS		N/A

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

With an ALUXX aluminum frame that's lightweight for climbing and strong enough for off-road use, the Boulder SE is equally capable on city streets or singletrack.



FEATURES

- SR XCM, 100mm suspension fork
- Shimano trigger shifting, Shimano Acera rear derailleur
- Alloy direct-pull brakes
- Giant XC Alloy/alloy hub, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
<i>inches</i>	<i>Red</i>	<i>Satin Black</i>	<i>degrees</i>	<i>degrees</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
XXS/12.5	331061	331161	70.0	75.0	20.5	4.6	16.7	39.7	28.1
XS/14	331062	331162	70.0	73.0	21.3	4.6	16.7	40.2	28.5
S/16	331063	331163	70.0	73.0	22.4	4.6	16.7	41.2	28.8
M/18	331064	331164	70.0	73.0	22.9	5.7	16.7	41.8	30.2
L/20	331065	331165	70.0	73.0	23.8	6.3	16.7	42.3	31.4
XL/22	331066	331166	70.0	73.0	24.3	7.5	16.7	43.1	31.9

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire

BOULDER SE W

EXPAND YOUR HORIZONS, EXPLORE NEW TERRAIN. WITH INCREASED CONTROL AND COMFORT, YOU'RE FREE TO FOLLOW THE TRAIL.



SPECIFICATIONS

FRAME	SIZES	14(XS),16(S), 18(M)	
	COLORS	Pearl White/Orange, Silver/Lavender	
	FRAME	ALUXX-Grade Butted Aluminum	
	FORK	SR XCM w/ Preload Adjust, 100mm travel	
	SHOCK	N/A	
COMPONENTS	HANDLEBAR	Steel, 50mm rise 25.4	
	STEM	Alloy	
	SEATPOST	Alloy, 350x30.9	
	SADDLE	Giant Sport MTB Womens	
	PEDALS	Nylon Platform	
	SHIFTERS	Shimano EF-50	
	FRONT DERAILLEUR	Shimano C-102	
DRIVETRAIN	REAR DERAILLEUR	Shimano Acera	
	BRAKES	Alloy Direct-Pull Cantilever	
	BRAKE LEVERS	Shimano EF-50	
	CASSETTE	Shimano 14x34, 7-speed	
	CHAIN	KMC Z51	
	CRANKSET	Suntour XCT V2, 28/38/48	
	BOTTOM BRACKET	SR Cartridge	
	WHEELS	RIMS	Giant Alloy 32H, Double Wall
		HUBS	Alloy, 32h
		SPOKES	Stainless Steel, 14g
TIRES		Kenda K-Rad, 26x2.1	
EXTRAS		N/A	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Get around town, or around trails with Boulder SE W's stable upright positioning and lightweight ALUXX aluminum frameset.



FEATURES

- SR XCM, 100mm suspension fork
- Shimano trigger shifting, Shimano Acera rear derailleur
- Alloy direct-pull brakes
- Giant XC Alloy/alloy hub, wheelsset

FRAME GEOMETRY

Actual Frame Size	Part Number	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
<i>inches</i>	<i>Silver/Lavender</i>	<i>Pearl White/Orange</i>	<i>degrees</i>	<i>degrees</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
XS14	331572	331672	70.5	74.0	20.7	4.6	16.7	40.0	25.3
S/16	331573	331673	70.5	73.0	21.6	4.6	16.7	41.2	28.1
M/18	331574	331674	70.0	73.0	22.9	5.7	16.7	41.8	28.7

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire